

ADHESIVE & GROUT SELECTOR

PROPERTIES	PREPARATION		FIXING					FINISHING		
	UNIVERSAL LEVELLING FLOOR SCREED	PRO 50 FIBRE LEVELLING FLOOR SCREED	STANDARD SET FLEX	TILE TO GYPSUM	RAPID SET FLEX	RAPID SET FLEX S1	THICK BED FLEX	FLEXIBLE GROUT (10KG)	4 IN 1 WALL & FLOOR GROUT (5KG)	4 IN 1 WALL SILICONE (310ML)
COLOUR	Grey	Grey	Grey/ White	Pink	Grey/ White	Grey/ White	Grey/ White	VARIOUS		
BED THICKNESS (MM)	0-8	3-50	3-6	3-6	3-6	2-10	5-25	N/A	N/A	N/A
SETTING TIME (HRS)	24	4	24	3	3	3	3	24	5	N/A
COVERAGE (M ²)**	≤5	0.24-3.92	2-4	4-8	2-4	2-4	0.5-3.5	7-15	7-15	8.6-17 (lm)
JOINT WIDTH (MM)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	3-12	1-8	4-25
FLOOR	*	*	*	*	*	*	*	*	*	*
WALL	-	-	*	*	*	*	-	*	*	*
INTERIOR	*	*	*	*	*	*	*	*	*	*
EXTERIOR	*	*	*	-	*	*	*	*	*	*
SUBSTRATES										
FLOOR										
SAND/CEMENT SCREED	*	*	*	-	*	*	*	*	*	*
ANHYDRITE/ GYPSUM SCREED	**	**	**	*	*	*	*	*	*	*
U/F HEATED SCREED/ UNDERTILE HEATING	*	*	*	*	*	*	*	*	*	*
UNDERTILE HEATING	*	*	*	*	*	*	*	*	*	*
GLAZED TILES	*#	*#	*#	-	*#	*#	*#	*	*	*
UNGLAZED TILES	*	*	*	-	*	*	*	*	*	*
VINYL TILES	**	**	**	-	**	**	**	*	*	*
PLYWOOD OVERLAY	**	**	**	-	**	**	**	*	*	*
CONSTRUCTION BOARD	**	**	**	-	**	**	**	*	*	*
WALLS										
SAND/CEMENT RENDER	-	-	*	-	*	*	-	*	*	*
PLASTERBOARD	-	-	**	-	**	**	-	*	*	*
CONSTRUCTION BOARD	-	-	*	-	*	*	-	*	*	*
PLYWOOD	-	-	**	-	**	**	-	*	*	*
PLASTER SKIM***	-	-	**	*	**	**	-	*	*	*
LEGEND										

* Use with Prime Bond.

Use with slurry bonding coat (2 parts adhesive to 1 part (Prime Bond)).

NB. All coverage rates are approximate and should not be considered legally binding. *NB. Subject to weight of tile covering.